

## How to Order Your Entry Door System

- **Determine Your Rough Opening Size:**

Width x Height:

W \_\_\_\_\_ x H \_\_\_\_\_

- **What is the Width of the Jamb:**

4-9/16"

5-1/4"

6-9/16"

Custom \_\_\_\_\_

- **Choose Your Door Type:**

Single

Double

- **Determine Door Handing and Swing:**

(As viewed from outside the home)

Right Hand

Left Hand

Inswing

Outswing

- **Will There Be Sidelites?**

(As viewed from outside the home)

Right Side

Left Side

Both Sides

No Sidelites

- **Will There Be a Transom?**

Rectangular

No Transom

Elliptical

See Lowe's Millwork Desk for Help  
With Placing Your Order!



TerraCourt Full Lite Shown in Dark Mahogany Finish.

## How to Measure Your Existing Rough Opening

1. Remove interior casing at both sides and top of your existing door unit (single or double) to reveal rough opening frame.
2. Measure the distance of the rough opening from inside the face of stud to inside of face of stud. ("A.") Figure 1 below. *Note: sidelites are shown for example only. Your existing opening may be a single door, double door or single door with one sidelite.*
3. Measure the distance of the rough opening from the subfloor (plywood or concrete) to the bottom of the header above the door. ("B.") Figure 1 below.
4. Write down these measurements to order the correct size unit for your existing rough opening.

Figure 1

